



NOTE:
1. DIMENSIONS ARE TO VIRTUAL SHARP CORNERS UNLESS OTHERWISE SPECIFIED.

DO NOT SCALE

COMPRESSOR SPECIFICATIONS

DISPLACEMENT PER REVOLUTION	154.9 cc / rev. (9.5cu.in. / rev.)
MAXIMUM ALLOWABLE R.P.M.	8000 R.P.M.
MAXIMUM ALLOWABLE CONTINUOUS R.P.M.	6000 R.P.M.
REFRIGERANT	R134a
OIL (SP-15)	300 cc (10.1 floz.)

CLUTCH SPECIFICATIONS

RATED VOLTAGE	DC 12V
BREAKAWAY TORQUE	3.5 kgf-m min. @ 12V
MINIMUM ENGAGEMENT VOLTAGE	7.5V @ AIR GAP 0.6mm REF
POWER CONSUMPTION	49 watts max.
BELT TYPE	PV6 TYPE
MAXIMUM ALLOWABLE BELT TENSION	90 kgf
PULLEY DIAMETER	Ø125 mm (4.92 in.)
CLUTCH TYPE	HEAVY DUTY

REV. LEVEL	RELEASED FOR ENGG DEVELOPMENT	<p>SANDEN INTERNATIONAL (U.S.A.), INC.</p> <p>This drawing and the information contained hereon are CONFIDENTIAL and PROPRIETARY to Sanden International (U.S.A.), Inc. are received in CONFIDENCE and shall not be used, copied, or disclosed to others without the written permission of Sanden International (U.S.A.), Inc.</p> <p>INTERPRETATION OF THIS DRAWING PER ASME Y14.5M-1994</p> <p>THIRD ANGLE PROJECTION</p> <p>MATERIAL: _____</p> <p>NAME _____</p> <p>COMPRESSOR</p> <p>DWG. NO. 4039-6000</p>	SCALE REF 1:1	PLOTTED SCALE REF 1:1	METRIC	
DSGN	M. Ballhagan		DATE	5/8/07	SIZE	D
CHK	Donna Lee		DATE	5/8/07		
APPV.	Ed Arruda					
RELEASED FOR PRODUCTION VAL'D.	M. Ballhagan		DATE	5/8/07		
REV. LEVEL	RELEASED FOR PRODUCTION					
DSGN	M. Ballhagan					
CHK	Donna Lee					
APPV.	Ed Arruda					
DATE	5/8/07					
REV. LEVEL	RELEASED FOR PRODUCTION					
DSGN	M. Ballhagan					
CHK	Donna Lee					
APPV.	Ed Arruda					
DATE	5/8/07					